

BNE-42/51S

Tornio a testa fissa

Items		BNE-42S6	BNE-51S6	BNE-42SY6	BNE-51SY6
Power Chuck	SP1/SP2	5"/5" hydraulic drive	6"/5" hydraulic drive	5"/5" hydraulic drive	6"/5" hydraulic drive
Maximum Machining Diameter of Bar Work	SP1	ø42mm	ø51mm	ø42mm	ø51mm
	SP2	ø42mm			
Standard Turning Length	SP1	90mm			
Type of Turret	HD1	12St.Turret			
	HD2	12St.Turret			
Slide Stroke	HD1	X1 axis	175mm		
		Z1 axis	380mm		
		Y axis	-	±40mm	
	HD2	X2 axis	145mm		
Z2 axis		175mm			
R spindle travel		450mm			
Shank Height of Square Tur-		□20mm			
Tool hole diameter		ø25mm			
Maximum Number of Revolving Tools		12			
		12			
Main spindle speed range	SP1	6,000min ⁻¹	5,000min ⁻¹	6,000min ⁻¹	5,000min ⁻¹
	SP2	5,000min ⁻¹			
Spindle motor	SP1	15/11kW			
	SP2	5.5/3.7kW			
Machine Height		1,925mm			
Floor Space		2,690×2,160mm			
Machine Weight		7,600kg	7,800kg	7,600kg	7,800kg

Citizen Machine Italia s.r.l.

Sede: Via Campo Romano, 13 • 24050 Spirano (BG) ITALY

TEL. + 39 035 877 738 • info@citizenmacchineitalia.it • www.citizenmacchineitalia.it