

RL03

Tornio a testa fissa

| Items | | RL03 |
|-------------------------------------|----------------------|-----------------------------|
| Power Chuck | Pneumatic | 3"(4") Precision Chuck |
| Diaphragm Chuck | Pneumatic | 4" |
| Maximum diameter of Collet Chuck | Stationary(with Pad) | ø35mm |
| Maximum diameter of Collet Chuck | Pull type(with Pad) | ø40mm |
| | | 50mm |
| Spindle motor | 15min./cont. | 2.2/1.5kW |
| Spindle Speed Range | | 80 - 8,000min ⁻¹ |
| Type of Turret | | Horizontal Linear Turret |
| Shank Height of Square Turning Tool | | □10mm, □12mm, (□16mm) |
| Diameter of Drill Shank | | ø20mm |
| Slide Travel | X axis | 180mm |
| | Z axis | 200mm |
| Machine Height | | 1,600mm |
| Spindle Center Height | | 875mm |
| Floor Space(Width × Length) | | 700mm×1,480mm |
| Machine Weight(Machine Body) | | 1,500kg |

Citizen Macchine Italia s.r.l.

Sede: Via Campo Romano, 13 • 24050 Spirano (BG) ITALY

TEL. + 39 035 877 738 • info@citizenmacchineitalia.it • www.citizenmacchineitalia.it