

BNA-42MSY

Tornio a testa fissa

| Items | BNA-42MSY | |
|--|-----------|-------------------------------------|
| Maximum Machining Diameter of Bar Work | SP1 | ø42mm |
| | SP2 | ø34mm |
| Maximum Machining Length | | 100mm |
| Spindle motor(15min./Cont.) | SP1 | 11/7.5kW |
| | SP2 | 5.5/3.7kW |
| Spindle speed | SP1 | 6,000min ⁻¹ |
| | SP2 | 5,000min ⁻¹ |
| Type of Turret | | 8St.Turret(half-indexing mechanism) |
| Shank Height of Square Turning Tool | | □20mm |
| Diameter of Drill Shank | | ø25mm |
| Rapid feed rate | Z1 axis | 20m/min |
| | X1 axis | 20m/min |
| | Y1 axis | 12m/min |
| | Z2 axis | 20m/min |
| | X2 axis | 12m/min |
| Maximum Number of Revolving Tool | | 8 |
| Machine Height | | 1,620mm |
| Floor Space | | 2,388x1,450mm |
| Machine Weight | | 3,000kg |

Citizen Machine Italia s.r.l.

Sede: Via Campo Romano, 13 • 24050 Spirano (BG) ITALY

TEL. + 39 035 877 738 • info@citizenmacchineitalia.it • www.citizenmacchineitalia.it